LF070.000.XX



OVERVIEW
70W power supply
Custom made

INPUT	
Universal Input	100-240Vac
Leakage current	<2mA /240VAC
Efficiency	>87%

OUTPUT	
Nominal Output Power	70W
Single Output available	12Vdc, 24Vdc, 36Vdc, 48Vdc

PROTECTIONS
Under/Overvoltage protection
Overload/Short circuit protection

CERTIFICATIONS Compliance with:				
EN62368	EN60950	EN60335	EN61558	IEC/EN 60335-2-75
IEC/EN 61000-3-2	IEC/EN 61000-4-2	IEC/EN 61000-4-4	IEC/EN 61000-4-6	IEC/EN 61000-6-2
IEC/EN 61000-3-3	IEC/EN 61000-4-3	IEC/EN 61000-4-5	IEC/EN 61000-4-11	IEC/EN 61000-6-3

CONNECTIONS	
Input	Terminal Block 2 PIN
Output	Terminal Block 2 PIN

DIMENSIONS AND WEIGHT	
Dimensions (L x W x H)	76 x 51 x 27 mm
Weight	~80g

EMC EMISSION Compliance with:
EN55032
GB9254
Class B
EN55014
EN61000-3-2,-3

EMC IMMUNITY Compliance with:
EN61000-4-2,3,4,5,6,8,11 EN61000-6-2 (EN50082-2)
heavy industry level, criterial A, EAC TP TC 020